

PCT WATER REPELLENT TECHNOLOGY_{CC}



"like water off a duck's back"

PCT[®] ADVANCE

PRODUCT CODE D-023

Revision 1.1

APPLICATION PROCEDURE

Revised
10/08/2014

SAFETY. Please consult SAFETY DATA SHEET S-023

SURFACE PREPARATION.

- Remove all loose and flaking paint.
- Remove all surface residue, powder or contaminants.
- Remove all vegetable growth (algae) with household detergent.
- Remove all excess water or moisture.

APPLICATION PROCEDURE.

Do not apply to a surface when continuous running water is evident due to broken or breached plumbing or poor drainage.. Repair the leakage.

Do not dilute.

Apply by brush or roller.

Spreading rate must not exceed 6m² per litre.

Avoid spillages.

Protect the surrounding area by means of drop sheets.

Wash equipment with clean potable water.

Leave for 24 hours before over coating.

The information contained in this document is meant as a guide for the specifier or user. It is gained from laboratory tests conducted in controlled environment and experience. No guarantee of performance is implied since application procedure, conditions of use, substrate condition and substrate cleanliness is beyond our control.

MANUFACTURED BY:

PCT WATER REPELLENT TECHNOLOGY CC

DISTRIBUTED BY:

MARVEL COATINGS
5 LOUIS TRICHARD STR
EXTENSION 10
WITBANK
1035

Tel: 013 656 4994

Fax: 086 623 7944

Cell: 072 404 1625

e-mail: info@marvelcoatings.co.za

web: www.marvelcoatings.co.za