



"like water off a duck's back"

PCT[®] X-TREME

PRODUCT CODE D-022

Revision 2.1

APPLICATION PROCEDURE

Revised
26/07/2014

SAFETY. Please consult SAFETY DATA SHEET S-022

APPLICATION INTERVAL.

The application interval of PCT X-TREME after plaster has been applied is subject to ambient humidity and temperature conditions which may vary in accordance with seasonal changes. It is also important to note that PCT X-TREME utilises inherent moisture to facilitate curing.

AMBIENT TEMPERATURE	INTERVAL
25 – 30 Degree "C"	4 hours
15 – 25 Degree "C"	6 hours
8 – 15 Degree "C"	8 hours

The above table is a guide only.

However, and from a practical viewpoint, PCT X-TREME may be applied to partly set plaster, but not disturbing the texture by the application method.

APPLICATION PROCEDURE.

Do not dilute.

Apply by brush or roller.

Spreading rate must not exceed 6m² per liter.

Avoid spillages.

Protect the surrounding area by means of drop sheets.

Wash equipment with clean potable water.

PAINTING INTERVAL

Apply the first paint coat after 8 hours of application of PCT X-TREME

The information contained in this document is meant as a guide for the specifier or user. It is gained from laboratory tests conducted in controlled environment and experience. No guarantee of performance is implied since application procedure, conditions of use, substrate condition and substrate cleanliness is beyond our control.

MANUFACTURED BY:

PCT WATER REPELLENT TECHNOLOGY CC

DISTRIBUTED BY:

MARVEL COATINGS
5 LOUIS TRICHARD STR
EXTENSION 10
WITBANK
1035
Tel: 013 656 4994
Fax: 086 623 7944
Cell: 072 404 1625
e-mail: info@marvelcoatings.co.za
web: www.marvelcoatings.co.za