



"like water off a duck's back"

PCT 56 WATER REPELLENT TECHNOLOGY

PRODUCT CODE D-003

APPLICATION PROCEDURE

REVISION 3
MARCH 5TH. 2014

SURFACE PREPARATION.

- Thoroughly remove all dust, dirt or any foreign debris.
- Ensure that the surface is dry.

APPLICATION.

- Ensure that the surrounding area, furniture, carpets, glazing, equipment, aluminium frames or any none ferrous material etc. is well covered and protected against spillages or overspray.
- Application equipment may consist of household pesticide trigger action spray applicator or high volume agriculture backpack. **BRUSH OR ROLLER APPLICATION IS NOT RECOMMENDED DUE TO LOW SURFACE TENSION OF THE PRODUCT.**
- Always commence application at the highest point by applying in short horizontal sweeps.
- Apply to the surface and ensure that the surface is saturated. Avoid damming on the surface.
- If damming does occur, remove immediately with a moist cloth.
- After application cut-off lines are identified by simply pouring water onto the surface.
- **Ensure that no damming occurs on the surface during application. Remove excess material immediately with a moist cloth.**

MAINTENANCE.

- PCT 56 WATER REPELLENT TECHNOLOGY is inorganic and will not require maintenance.

The information contained in this document is meant as a guide for the specifier or user. It is gained from laboratory tests conducted in controlled environment and experience. No guarantee of performance is implied since application procedure, conditions of use, substrate condition and substrate cleanliness is beyond our control.

MANUFACTURED BY:
PCT WATER REPELLENT TECHNOLOGY CC
UNIT 4 BRETT'S LANE
DUNCANVILLE
GAUTENG
SOUTH AFRICA
1935
TELEFAX +27(0)86 663 4056
+27(0)86 572 8082
MOBILE +27(0)79 900 2234
E-MAIL attie@pctwaterrepellent.com
WEB www.pctwaterrepellent.co.za